



NOTES:

PERMANENT PAVEMENT REPLACEMENT SHALL NOT BE PERFORMED UNTIL SO ORDERED BY THE ENGINEER.

EDGES OF THE EXISTING PAVEMENT SHALL BE CUT VERTICAL AND TRIMMED TO PROVIDE A STRAIGHT LINE JUNCTURE BETWEEN EXISTING AND NEW PAVEMENT. NO RAGGED EDGES SHALL BE PERMITTED.

GRANULAR BACKFILL SHALL BE COMPACTED PER 912. IT SHALL BE SHAPED AND COMPACTED AS DIRECTED BY THE ENGINEER.

VERTICAL FACES OF EXISTING ASPHALT PAVEMENT AND THE SUBBASE SHALL BE CLEANED AND COATED WITH BITUMINOUS MATERIAL IN ACCORDANCE WITH 401.12.

SURFACE JOINTS SHALL BE SEALED BY AN APPLICATION OF 409.02 BITUMINOUS MATERIAL FOLLOWED BY AN APPLICATION OF 407.02 COVER AGGREGATE.

APPROVED _____ _____ CITY ENGINEER	TYPICAL PAVEMENT REPLACEMENT FOR TRENCHES	CITY OF LANCASTER, OHIO DEPARTMENT OF ENGINEERING	
REVISED: 3/5/07		STANDARD CONSTRUCTION DRAWING DWG. BY: ...MAC... FILE NUMBER CHK'D BY: W-1B	